

PRODUCT DATA SHEET

SO-CHEM D- 601 DEFOAMER

GENERAL DESCRIPTION

So-Chem D- 601 Defoamer is an oil soluble product. The main ingredient is Polydimethylsiloxane (<10%). This product is specially formulated to control foam formation in crude oil processing systems and liquids under pressure.

APPLICATION

In crude oil processing systems the production of foam due to entrained gases in the crude oil can result in serious operational problems such as:

1. Shutdown of the process due to “false” high liquid level in separators.
2. Cavitation of discharge pumps.
3. Overflow of production tanks.

So-Chem D- 601 Defoamer can be used to effectively eliminate the above operational problems when injected into the production stream, tank tops or wherever foam is present in a process system.

So-Chem chemical personnel can advise on treatment and application volumes.

TYPICAL PHYSICAL PROPERTIES:

Specific Gravity	0.80
Flash Point	38 ° C/ 100.0 ° F
Solubility	Oil Soluble
Appearance	Straw yellow Liquid
Odor	Kerosene

SOUTHERN CHEMICALS LIMITED

1 - 2 Tarran Industrial Estate La Romain

TEL NO: ((868) 230- 6081

E-mail: sochemltd@flowtrinidad.com/sochemltd@hotmail.com

HANDLING

So-Chem D- 601 Defoamer is an industrial chemical. Observe the warning label on product container. Normal precautions for industrial chemicals apply. For detailed information, consult the Safety Data Sheet which can be available upon request.

AVAILABILITY

So-Chem D- 601 Defoamer is available in 55 gallon drums from Southern Chemicals Limited, #2 Tarran Industrial Estate San Fernando.

SOUTHERN CHEMICALS LIMITED

1 - 2 Tarran Industrial Estate La Romain

TEL NO: ((868) 230- 6081

E-mail: sochemltd@flowtrinidad.com/sochemltd@hotmail.com